

Uplight



| | Ø80mm | = 3.45mm |
|-------|---------------|----------------|
| 108mm | | |
| | I 8mm S0mm | 17.5mm |

| SPECIFICATIONS | |
|-----------------------|------------------------------|
| Product Code | AQL-530 |
| Family | Phoenix |
| Construction Material | Solid Cast Brass |
| Cable | 1M Aqualux PLUS QuickConnect |
| IP Rating | IP68 |
| Warranty | 5 Year Aqualux Warranty |

| CONFIGURED OPTIONS | | |
|--------------------|--------------------------|--|
| Variant Code | AQL-530-B5X0045710Q | |
| Body Colour | Copper | |
| Control Gear | 12~24V AC / 24V DC | |
| Rated Power | 4W | |
| Nominal Lumens | 320 lm | |
| CCT / Colour | 5700K / 300mA | |
| Optical | 10 | |
| CRI | 80 | |
| Other | AqualuxPLUS QuickConnect | |
| Dimming | Optional 10V PWM (DC) | |

INTRODUCTION

Sharing many of the same components as the AQL-540, the AQL-530 is designed to withstand the worst conditions nature can offer. Solid cast brass with 4 finish options and epoxy encapsulated internals the AQL-530 is suitable for any application that requires the best in reliability and performance.



1300 662 644 sales@aqualux.com.au