


# LED TRI-CCT OYSTER LIGHTS



## PRODUCT FEATURES:


- Input voltage range: 220-240V AC 50/60Hz
- Constant current inbuilt driver output voltage: 60-80V DC
- Base: metal
- Diffuser: PS
- LED chips: SMD2835 LED
- Power factor: >0.9
- Colour temp changeable: 3000K/4000K/5000K
- CRI: 80
- Ambient Temp: -20 to 40°C
- Suitable for dimming
- Suitable for 2-way switching
- Suitable for use with 3 wire motion or microwave sensors
- Changes to appearance due to climatic conditions not covered under warranty




30,000hr Lifetime	150° Beam Angle	<b>IP44</b> Rated	DIMMABLE	<b>3YEAR</b> Replacement Warranty
-------------------	-----------------	-------------------	----------	-----------------------------------

## Tested & Recommended Dimmers:


Brand	Part No.	PCS Per Dimmer
CLA	LYNX, VELA	OYSDIM003: 1-9pcs OYSDIM004: 1-7pcs OYSDIM005: 1-5pcs
HPM	CAT250T, CAT400T & CAT250L	
DIGINET	MEDM & MMEM/RT	
CLIPSAL	32E450UDM, 31E2PUDM, 32E450LM, 32ELEDM-WE & 32E450TM	



OYSDIM003



OYSDIM004



OYSDIM005

Part No.	Description	Kelvin	Lumens	Watt	CRI	Diam	Back Plate	Weight	Box	Carton QTY
OYSDIM003	OYSTER LED DIMM WH Trim RND 12W Multi	3000/ 4000/ 5000K	960/ 1140/ 1020lm	12W	80	Ø290mm	Ø259.3mm	0.6kg	30x30x10cm	1/10
OYSDIM004	OYSTER LED DIMM WH Trim RND 18W Multi	3000/ 4000/ 5000K	1400/ 1650/ 1500lm	18W	80	Ø350mm	Ø320mm	0.85kg	37x37x11cm	1/10
OYSDIM005	OYSTER LED DIMM WH Trim RND 24W Multi	3000/ 4000/ 5000K	1700/ 2000/ 1800lm	24W	80	Ø410mm	Ø380mm	1.1kg	42x42x11cm	1/8