

Cougar Lighting Pty Ltd

Product Specification Sheet

Name	FAHRENHEIT	Checked
Model Number	FAH24WPL	
Description	Fahrenheit PL 24W Wall Light	
Finish	Chrome (Steel)	
Glass	2 x Frost Glass Panel L: 413mm W: 64mm 4mm thick	

COMPONENT VERIFICATION

Component	Manufacturer	Model No	Technical Data	Standard	Marks of Conformity
Lampholder	Ningbo Economic & Technical	2G11	AC 250V, 2A, 140°C, Screwless Terminal	Annex 1 of Council Directive 2006/95/EC	TUV
Terminal Block	Heavy Power Co Ltd	PA7	WhitePlastic 3 Pole 450V 17.5A	EN 60998-2-1:2004	VDE CERT NO: 40019839
Earth Internal Wiring Active & Neutral	Shenzhen Mysun Insulation Materials	HO5S-K	Silicon Rubber, 1 x 0.75mm ² , 450V, 180°C	DIN VDE 0282:2005-02	VDE CERT NO: 40016705
	Guangzhou Feng Tai Electronics	FT-FEP-102 VDE REG NO:7997	Single Core 1 x 0.5mm ² 300/500V	EN 60228:2005	VDE CERT NO: 40013289
Driver/Ballast	Shenzhen City Hengyao Lighting Co. (3AAA)	YZ-124EAA	220-240V. 50-60Hz. PLL 1 x 24W 0.106A	AS/NZS 61347.2.3:2004	SAA110575EA C-TICK NO: N2816
Globe supplied	Xieguang Electronics Co. Ltd	H-24	Single Capped 24W 2700k	EN55015:2000+A1:2001 EN61547:1995+A1:2000	CE

Globe Description PL 24W 2700k (Compact 2 Tube) TC-L

Relamping Label PL 24W MAX (On backplate next to tube)

Dimensions **Backplate H:** 60mm **W:** 32mm **L:** 240mm **Housing:**
H: 60mm **W:** 70mm **L:**420mm **Overall H:** 60mm **L:** 420mm **P:** 100mm

Wiring Layout Double insulated **single core active & neutral conductors only**, from terminal block to the ballast. Double insulated **single core active & neutral conductors only** from the ballast to the lamp holder. Active & neutral conductors have white heat protective shrink covering them. **Earthed from the ballast to the backplate & backplate to the terminal block. Earth wire to ballast must be BRASS CRIMPED. NO SOLDER**

Mounting & Construction Metal rail that mounts to wall holds to the backplate by 2crews. 2 x Frost glass panels that cover the PL lamp & lampholder, top and bottom, held to the chrome housing by chrome screws. The PL ballast is mounted inside the backplate.

IP Rating N/A

Weather Proofing N/A

Drainage Hole N/A

Cable Entry Hole 19mm hole in white metal mounting rail, white rubber grommet 18mm.

Labels

1. Rating Label

COUGAR LIGHTING
MODEL NO: FAH24WPL
240V 50Hz MAX PL 24 WATT
THIS LUMINAIRE MUST BE INSTALLED
BY A LICENSED ELECTRICIAN
MADE IN CHINA

2. IP Integrity Label
N/A

3. AEN Label
Imprinted on black plastic pad underneath terminal block.

4. Earth Label
Earth label is to be placed close to the earth wire internally

Label Position
1. The Rating Label ,4. Earth Label should all be mounted inside the backplate. 3. AEN Label should be on plastic terminal block pad.

Packing 2 Ply White box with 30cm x 10cm colour label. Fitting packed in plastic bag. Polystyrene inside box.

Barcode 9305125007059

Accessory 2 x plaster screws.

Instructions Yes

Design Specification AS/NZS 60598.2.1

Warranty 12 month (excluding tube).

Image:

Comments:

- 1) ALL WIRING MUST AS SPECIFIED.
- 2) 3AAA BALLAST MUST HAVE SAA NO. & OUR C-TICK NO ON IT.
- 3) NO SOLDER TO BE USED ON ENDS OF WIRING.
- 4) MUST BE EARTHED AS PER OUR WIRING INSTRUCTIONS ABOVE.

Checked

