



# Stockholm

LED
CRI 80
3000K 4000K
IP 44
IP 65
DIMMABLE

Recommended dimmers: Clipsal LED

Anodized Titanium finish | Clear glass

IP65 Spike, 1lt Adj & 2lt Wall  
IP44 2lt/3lt & 4lt Rail

Available as Frame only  
or with GU10 LED globes  
12v Spike light not dimmable

Rail Measurements  
2lt R L 300mm W 50mm P 25mm  
3lt R L 500mm W 50mm P 25mm  
4lt R L 640mm W 50mm P 25mm

Model No	Description	Light Source	Lumens	Dimensions
STO1ST 3000K, 4000K	1lt 12v LED Exterior Spike Light	1 x MR16 5w globe	430Lm/460Lm	H: 650mm W: 60mm P: 130mm
STO1WT 3000K, 4000K	1lt LED Exterior Adjustable Wall Light	1 x GU10 5w globe	450Lm/470Lm	H: 160mm W: 68mm P: 160mm
STO2WT 3000K, 4000K	2lt LED Exterior Wall Light	2 x GU10 5w globes	900Lm/940Lm	H: 205mm W: 68mm P: 86mm
STO2RT 3000K, 4000K	2lt LED Exterior Rail	2 x GU10 5w globes	900Lm/940Lm	L: 360mm W: 60mm P: 170mm
STO3RT 3000K, 4000K	3lt LED Exterior Rail	3 x GU10 5w globes	1350Lm/1410Lm	L: 560mm W: 60mm P: 170mm
STO4RT 3000K, 4000K	4lt LED Exterior Rail	4 x GU10 5w globes	1800Lm/1880Lm	L: 700mm W: 60mm P: 170mm