NO UV/IR



NEO-PRO-25 LED Recessed Downlight

Description

The NEO-PRO range of LED downlights are the latest upgrade to the NEO Series, with improved functions such as TRIO Tri-colour switchable technology as well as a higher IP Rating for wet areas. Designed to reduce glare as well as maintaining high performance in light output and energy consumption. LED recessed downlight with anti-glare deep set frame, frosted diffuser, and an integrated dimmable LED driver with flex & plug. Fully dimmable with suitable dimmers.

Now with TRIO, the added option of changing the colour temperature output of the downlight with a dip switch at the back of the fitting.



ies

3yr


65

LED

Specification Features

opecification reactines				
Input Voltage:	240V			
Power (W):	25			
IP rating (IP):	IP65			
Lumens (lm):	Warm White 3000K - 2250lm			
	Neutral White 4000K - 2400lm			
	White 5700K - 2300lm			
LED type:	SMD			
CCT:	3000K - 4000K - 5700K			
CRI:	≥80			
Beam angle (°):	90°			
Dimmable:	Yes*			
Lifespan (hrs):	50,000hrs			
Cutout (Ø):	Ø150-165mm			
*Fully dimmable with suitable dimmers.				

Diagrams / Additional



IC-4

Item No.	Variant		CCT
item 140.	Wht	Blk	CCI
	20918	20917	TRIO
NEO-PRO-25-REC	DALI		
	21609	21610	TRIO

Cutout: Ø150-165mm

Domus 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: enquiries@domuslighting.com.au Specification subject to change without prior notice.

Ø172mm