











VIPER Strip Kits

- Viper LED flexible strip light kits
- Dimmable using Havit LED controllers
- Peel and stick backing for initial placement
- Complete with LED driver with flex and plug
- Beam angle 120 degrees
- All LED strip must be installed using anti-static measures and on an aluminium heat dissipating surface for warranty purposes (HV9705-1003 or HV9705-1603)







Image for illustration purposes only.

4.8w 3000K LED Strip Lighting Kits

IMAGE	LENGTH	PART NUMBER	SMD	IP RATING	LED PER METRE	LUMENS PER METRE	VOLTAGE	POWER	TOTAL WATTAGE
 + 	2 mtr	VPR9733IP54-60-2M	3528	IP54	60	390lm	12v DC	4.8w/m	9.6w
 + 	5 mtr	VPR9733IP54-60-5M	3528	IP54	60	390lm	12v DC	4.8w/m	24w
 + 	10 mtr	VPR9733IP20-60-10M	3528	IP20	60	390lm	24v DC	4.8w/m	48w
 + 	10 mtr	VPR9733IP54-60-10M	3528	IP54	60	390lm	24v DC	4.8w/m	48w

14.4w 3000K LED Strip Lighting Kits









IMAGE	LENGTH	PART NUMBER	SMD	IP RATING	LED PER METRE	LUMENS PER METRE	VOLTAGE	POWER	TOTAL WATTAGE
 + 	2 mtr	VPR9783IP54-60-2M	2835	IP54	60	1200lm	12v DC	14.4w/m	28.8w
 + 	5 mtr	VPR9783IP54-60-5M	2835	IP54	60	1200lm	12v DC	14.4w/m	72w







All LED strip must be installed on an aluminium heat dissipating surface

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 275 - 282. Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 362









4.8w 4000K LED Strip Lighting Kits

IMAGE	LENGTH	PART NUMBER	SMD	IP RATING	LED PER METRE	LUMENS PER METRE	VOLTAGE	POWER	TOTAL WATTAGE
 + 	2 mtr	VPR9735IP54-60-2M	3528	IP54	60	410lm	12v DC	4.8w/m	9.6w
 + 	5 mtr	VPR9735IP54-60-5M	3528	IP54	60	410lm	12v DC	4.8w/m	24w
 + 	10 mtr	VPR9735IP20-60-10M	3528	IP20	60	410lm	24v DC	4.8w/m	48w
 + 	10 mtr	VPR9735IP54-60-10M	3528	IP54	60	410lm	24v DC	4.8w/m	48w





14.4w 4000K LED Strip Lighting Kits

IMAGE	LENGTH	PART NUMBER	SMD	IP RATING	LED PER METRE	LUMENS PER METRE	VOLTAGE	POWER	TOTAL WATTAGE
 + 	2 mtr	VPR9785IP54-60-2M	2835	IP54	60	1260lm	12v DC	14.4w/m	28.8w
 + 	5 mtr	VPR9785IP54-60-5M	2835	IP54	60	1260lm	12v DC	14.4w/m	72w

4.8w 5500K LED Strip Lighting Kits

IMAGE	LENGTH	PART NUMBER	SMD	IP RATING	LED PER METRE	LUMENS PER METRE	VOLTAGE	POWER	TOTAL WATTAGE
 + 	2 mtr	VPR9734IP54-60-2M	3528	IP54	60	430lm	12v DC	4.8w/m	9.6w
 + 	5 mtr	VPR9734IP54-60-5M	3528	IP54	60	430lm	12v DC	4.8w/m	24w
 + 	10 mtr	VPR9734IP20-60-10M	3528	IP20	60	430lm	12v DC	4.8w/m	48w
 + 	10 mtr	VPR9734IP54-60-10M	3528	IP54	60	430lm	12v DC	4.8w/m	48w

14.4w 5500K LED Strip Lighting Kits

IMAGE	LENGTH	PART NUMBER	SMD	IP RATING	LED PER METRE	LUMENS PER METRE	VOLTAGE	POWER	DIMMABLE
 + 	2 mtr	VPR9784IP54-60-2M	2835	IP54	60	1320lm	12v DC	14.4w/m	28.8w
 + 	5 mtr	VPR9784IP54-60-5M	2835	IP54	60	1320lm	12v DC	14.4w/m	72w



All LED strip must be installed on an aluminium heat dissipating surface

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 275 - 282. Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 362