





## **40W TRICOLOUR LED BATTEN LIGHT**

**TLDB34640** 



This Tricolour LED batten features an energy efficient tubeless design as well as a shatter resistant polycarbonate diffuser. Making this batten ideal for use in carparks, garages, security areas, workshops, factories, industrial environments, stairwells, corridors, storage areas, schools and public amenities.

- Lightweight powder coated aluminium housing
- Surface mount directly to ceiling without visible brackets
- Shatter resistant polycarbonate diffuser
- Direct mounting (no brackets required)
- 40W Tricolour LED light



LED

Main body

& screw pack







Angle








#### **INCLUDES**

#### **DIMENSIONS**



**AAI** Figure Flux out: 2422 1m 350.8,11141x 292.77c 87.70,278.41x 585.54cn 38.98,123.71 878.31cm 21.92,69.611> Height Eavg,Emax Angle:111.32dec

Product No: TLDB34640 AAI Figure at 40000k CCT

# **Luminous Intensity Distribution Diagram**

C Range: 0 - 360DEG C Interval: 22.5DEG Test Speed: HIGH Temperature: 25.3DEG AVERAGE BEAM ANGLE(50%):130,2 DEG

Product No: TLDB34640 Luminous Intensity Measure at 4000k CCT





Aust/NZ Approval No. EESS-190475-0



9312375506737







#### **TLDB34640**

#### **40W TRICOLOUR LED BATTEN LIGHT**

#### **FEATURES**

- Surface mounted LED batten light
- Lightweight powder coated aluminium housing
- Shatter resistant polycarbonate diffuser
- Direct mounting (no brackets required)
- Provides excellent light distribution using Tricolour SMD LED technology
- Select either 3000k, 4000k, or 6500k light colour temperature setting

#### **SPECIFICATIONS**

Model name	40W Tricolour LED Batten Light 1230mm	
Model number	TLDB34640	
Power (wattage)	40W	
Voltage	220v-240v	
Frequency	50Hz	
Switchable Tricolour lumens	4000lm max	
Colour temperature	3000k / 4000k / 6500k	
LED light beam angle	110°-130°	
Product size (mm)	1230 x 75 x 85	
Material	Shatter resistant polycarbonate diffuser	
LED Type	SMD LED	
CRI	≥80	
Approximate lamp life	30,000hrs	
Weather resistance rating	IP20	
Operating temperature	-20°C to +40°C	



#### **INSTALLATION**

Installation	By licensed electrician only	
Warranty	2 year replacement warranty*	
* For further information regarding warranty terms and conditions, places refer to		

<sup>\*</sup> For further information regarding warranty terms and conditions, please refer to enclosed warranty statement.

#### SHIPPING

Packaging size	1276 x 88 x 85mm
Gross weight	9.4kg
Carton qty	4

### **AVAILABLE IN WHITE**



Model	Colour	Barcode
TLDB34640	White	9312375506737

