



# Vibe Recessed LED Wall Light 3W, 3K W/O Driver White

#### VBL-E06-3K-WHT



Our 3W, 3000K White Trim Accent 200 Recessed Wall Light is ultra thin. At 105mm tall, it provides a clean lined shape light for architectural lighting. Requires a remote 700mA LED constant current driver. Has a rating of IP20, a 50,000 hour lifespan and a 3 year warranty.

#### **Features & Benefits**

- Ultra slim and sleek recessed architectural LED wall light
- Equipped with OSRAM LED chips
- 80° beam angle
- Remote 350mA/700mA LED constant current driver required (Ordered separately)
- 50,000 hour lifespan
- 3 year warranty




## **Specifications**

Luminaire efficacy  EAN  9340994018485  Light Colour  Warm White  3 W  Lumen output  102 Im  IP rating  20  CRI  90  Beam Angle  80 Degrees  Trim colour  White  Cut out  100x30 mm  Length  35 mm  Width  32 mm  Height  105 mm  Lifespan  50000 Hours  Warranty  3 Years  Dimmable  Output current  350 mA  Constant current/voltage  Mounting type  LED source  Osram Olson  Material  Accessories  LeD  Input voltage  Volt AC 50HZ  Wiring method  Working temperature  -20°C ~40°C  Kelvin	SKU	VBL-E06-3K-WHT
Light Colour Warm White Wattage 3 W Lumen output 102 lm IP rating 20 CRI 90 Beam Angle 80 Degrees Trim colour White Cut out 100x30 mm Length 35 mm Width 32 mm Height 105 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Non-Dimmable Output current 250 mA Constant current/voltage Mounting type LED source Material Aluminium Accessories Lamp Type Input voltage Wiring method Working temperature -20°C ~40°C		
Light Colour Warm White Wattage 3 W  Lumen output 102 Im IP rating 20 CRI 90 Beam Angle 80 Degrees Trim colour White Cut out 100x30 mm Length 35 mm Width 32 mm Height 105 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Output current Constant current/voltage Mounting type LED source Material Aluminium Accessories Lamp Type Input voltage Working temperature Value Varmanty Varma	-	
Wattage 3 W Lumen output 102 Im  IP rating 20 CRI 90 Beam Angle 80 Degrees Trim colour White Cut out 100x30 mm Length 35 mm Width 32 mm Height 105 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Non-Dimmable Output current 350 mA  Constant current/voltage Mounting type Recessed LED source Osram Olson Material Aluminium Accessories Driver & Remote Lamp Type LED Input voltage Working temperature -20°C ~40°C	=7111	33 1000 1000 100
Lumen output  IP rating  CRI  Beam Angle  80 Degrees  Trim colour  White  Cut out  100x30 mm  Length  35 mm  Width  32 mm  Height  Lifespan  50000 Hours  Warranty  Dimmable  Output current  Constant current/voltage  Mounting type  LED source  Material  Accessories  Lamp Type  Input voltage  Wiring method  Working temperature  20  Constant  Constant Current  Hardwire  40  Working temperature		
IP rating CRI Beam Angle Beam Angle Trim colour White Cut out 100x30 mm Length 35 mm Width 32 mm Height 105 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Output current 350 mA  Constant current/voltage Mounting type LED source Osram Olson Material Accessories Lamp Type Input voltage Working temperature Vhite 100x30 mm Lifespan Vhite 100x30 mm Constant Const	Wattage	
CRI 90  Beam Angle 80 Degrees  Trim colour White Cut out 100x30 mm  Length 35 mm  Width 32 mm  Height 105 mm  Lifespan 50000 Hours  Warranty 3 Years  Dimmable Non-Dimmable Output current 350 mA  Constant current/voltage  Mounting type Recessed  LED source Osram Olson  Material Aluminium  Accessories Driver & Remote  Lamp Type LED  Input voltage Ya0 Volt AC 50HZ  Wiring method Hardwire  Working temperature -20°C ~40°C	•	102 lm
Beam Angle  Trim colour  Cut out  Length  35 mm  Width  32 mm  Height  Lifespan  50000 Hours  Warranty  3 Years  Dimmable  Output current  Constant current/voltage  Mounting type  LED source  Material  Accessories  Lamp Type  Input voltage  Working temperature  White  Wookan  White  80 Degrees  White  80 Degrees  White  Conx30 mm  Conx30 mm  Consm  Constant Corrent  Constant Current  Constant Current  Recessed  LED source  Driver & Remote  LED  Input voltage  Volt AC 50HZ  Wiring method  Hardwire  Vorking temperature	IP rating	20
Trim colour  Cut out  100x30 mm  Length  35 mm  Width  32 mm  Height  105 mm  Lifespan  50000 Hours  Warranty  3 Years  Dimmable  Non-Dimmable  Output current  350 mA  Constant current/voltage  Mounting type  LED source  Material  Accessories  LED  Input voltage  Wiring method  Working temperature  Wiring method  105 mm  Constant Current  Constant Current  Constant Current  Recessed  LED  LED  LED  LED  LED  LED  LED  LE	CRI	90
Cut out  Length  35 mm  Width  32 mm  Height  105 mm  Lifespan  50000 Hours  Warranty  3 Years  Dimmable  Non-Dimmable  Output current  Constant current/voltage  Mounting type  LED source  Material  Accessories  Lamp Type  Input voltage  Working temperature  100×30 mm  20 mm  Accessories  Dimmable  105 mm  50000 Hours  A Years  Constant Current  Constant Current  Constant Current  Aluminium  Accessed  LED  Input voltage  LED  Input voltage  Volt AC 50HZ  Hardwire  Working temperature  -20°C ~40°C	Beam Angle	80 Degrees
Length 35 mm  Width 32 mm  Height 105 mm  Lifespan 50000 Hours  Warranty 3 Years  Dimmable Non-Dimmable  Output current 350 mA  Constant current current/voltage Recessed  LED source Osram Olson  Material Aluminium  Accessories Driver & Remote  Lamp Type LED  Input voltage 240 Volt AC 50HZ  Wiring method Hardwire  Working temperature -20°C ~40°C	Trim colour	White
Width 32 mm  Height 105 mm  Lifespan 50000 Hours  Warranty 3 Years  Dimmable Non-Dimmable  Output current 350 mA  Constant current/voltage  Mounting type Recessed  LED source Osram Olson  Material Aluminium  Accessories Driver & Remote  Lamp Type LED  Input voltage 240 Volt AC 50HZ  Wiring method Hardwire  Working temperature -20°C ~40°C	Cut out	100x30 mm
Height 105 mm  Lifespan 50000 Hours  Warranty 3 Years  Dimmable Non-Dimmable  Output current 350 mA  Constant current/voltage  Mounting type Recessed  LED source Osram Olson  Material Aluminium  Accessories Driver & Remote  Lamp Type LED  Input voltage 240 Volt AC 50HZ  Wiring method Hardwire  Working temperature -20°C ~40°C	Length	35 mm
Lifespan 50000 Hours  Warranty 3 Years  Dimmable Non-Dimmable Output current 350 mA  Constant current/voltage Constant Current  Mounting type Recessed  LED source Osram Olson  Material Aluminium  Accessories Driver & Remote  Lamp Type LED  Input voltage 240 Volt AC 50HZ  Wiring method Hardwire  Working temperature -20°C ~40°C	Width	32 mm
Warranty Dimmable Non-Dimmable Output current 350 mA  Constant current/voltage Mounting type LED source Material Accessories Lamp Type Input voltage Working temperature  350 mA  Constant Current Current  Constant Current  Accessed  Dosram Olson  Aluminium  Accessories LED  Input voltage  240 Volt AC 50HZ  Hardwire  Vorking temperature  -20°C ~40°C	Height	105 mm
Dimmable  Output current  350 mA  Constant current/voltage  Mounting type  LED source  Material  Accessories  Lamp Type  Input voltage  Wiring method  Working temperature  Non-Dimmable  Aconstant  Constant Current  Constant Current  Accessed  Recessed  Aluminium  Aluminium  Accessories  LED  Input voltage  240 Volt AC 50HZ  Hardwire  Working temperature  -20°C ~40°C	Lifespan	50000 Hours
Output current  Constant current/voltage  Mounting type  Recessed  LED source  Material  Accessories  Lamp Type  Input voltage  Wiring method  Working temperature  350 mA  Constant Current  Recessed  Aluminium  Aluminium  Accessories  Driver & Remote  LED  Hardwire  Vorking temperature  -20°C ~40°C	Warranty	3 Years
Constant current/voltage  Mounting type Recessed LED source Osram Olson Material Accessories Driver & Remote Lamp Type LED Input voltage Viring method Working temperature  Constant Current Recessed LED Source Osram Olson LED LED Hardwire LED LED Hardwire Vorking temperature -20°C ~40°C	Dimmable	Non-Dimmable
Constant Current  Mounting type Recessed LED source Osram Olson Material Accessories Driver & Remote Lamp Type LED Input voltage Viring method Working temperature Constant Current Recessed Lecurity LED Aluminium Accessories LED Hardwire Hardwire Vorking temperature -20°C ~40°C	Output current	350 mA
LED source  Material  Accessories  Lamp Type  Input voltage  Wiring method  Working temperature  Osram Olson  Aluminium  Accessories  Driver & Remote  LED  Hardwire  Hardwire  -20°C ~40°C		Constant Current
Material Aluminium  Accessories Driver & Remote  Lamp Type LED  Input voltage 240 Volt AC 50HZ  Wiring method Hardwire  Working temperature -20°C ~40°C	Mounting type	Recessed
Accessories  Driver & Remote  LED  Input voltage  Viring method  Working temperature  Driver & Remote  LED  Hardwire  40 Volt AC 50HZ  Hardwire	LED source	Osram Olson
Lamp Type Input voltage 240 Volt AC 50HZ Wiring method Hardwire Working temperature -20°C ~40°C	Material	Aluminium
Input voltage 240 Volt AC 50HZ Wiring method Hardwire Working temperature -20°C ~40°C	Accessories	Driver & Remote
Wiring method Hardwire Working temperature -20°C ~40°C	Lamp Type	LED
Working temperature -20°C ~40°C	Input voltage	240 Volt AC 50HZ
	Wiring method	Hardwire
Kelvin 3000K	Working temperature	-20°C ~40°C
	Kelvin	3000K



### **Dimensional Drawings**



Photometric information available upon request.

