



## **VBLST-192WW-54**



Our 19.2W/m, 24V, 3000K, IP54, CRI90+ LED Strip lighting is a popular, versatile light source that will assist in creating inspiring lighting solutions. Due to being relatively inexpensive, easy to install and extremely flexible - LED strip lights are an ideal choice to enhance the mood in modern or contemporary architecture. The VIBE Range offers a huge variety of LED strip lights to choose from in different lengths, colours, and IP Ratings - with a host of accessories and aluminium extrusions to bring your design to life. Ask your VIBE Reseller about custom cut and assembly options for faster, easier installation on-site.

## **Features & Benefits**

- High efficiency SMD LED chips
- Customisable strip suited to multiple applications
- Colour Temperature: 3000K/4000K/6000K/RGB
- IP20/IP54 rated
- 3M adhesive taper
- 120° Beam angle
- 50,000 hours lifespan
- 3 years warranty ALL LED Strip must be installed on an aluminium heat dissipating surface for warranty purposes.



## **Specifications**

| SKU                      | VBLST-192WW-54                               |
|--------------------------|--|
| Luminaire efficacy       | 112 lm/W                                     |
| EAN                      | 9340994023779                                |
| Light Colour             | Warm White                                   |
| Wattage                  | 19.2 W                                       |
| Lumen output             | 2142 lm                                      |
| IP rating                | 54   |
| CRI                      | 90   |
| Beam Angle               | 120 Degrees                                  |
| Cut out                  | 29.4mm Cutting Intervals,<br>Spaced 4.2mm mm |
| Length                   | 5000 mm                                      |
| Width                    | 8 mm   |
| Height                   | 2 mm   |
| Lifespan                 | 50000 Hours                                  |
| Warranty                 | 3 Years                                      |
| Dimmable                 | Dimmable                                     |
| Constant current/voltage | Constant Voltage                             |
| LED source               | SMD  |
| Accessories              | VBLST-CTRL-BOX and VBLST-CTRL-DIM            |
| Lamp Type                | LED  |
| Dimming                  | PWM  |
| Input voltage            | 24 Volt DC                                   |
| Wiring method            | Fly Leads                                    |
| Weatherproof             | Weatherproof                                 |
| Working temperature      | -20°C ~ 45°C                                 |
| Kelvin                   | 3000K  |



Photometric information available upon request.

